

## **AKZ9 6230 NB**

12NC/Fx: 859991530390

## GTIN (EAN) code: 8003437833793

DIMENSION	<b>MEAS</b>	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	10	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	30	mm
Minimum area for inbound ventilation cavity (tall cabinet)	150	cm <sup>2</sup>
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	150	cm <sup>2</sup>
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	30	mm
Minimum area for inbound ventilation cavity (base cabinet)	150	cm <sup>2</sup>
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	150	cm <sup>2</sup>

Height of the front 595 mm Width of the front 595 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 41 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance in height is adjustable When product panel is missing, set to 0 product panel is missing area of appliances and lower handle product panel is missing area of appliances and lower handle product product panel is missing area of appliances and lower handle product product panel is missing area of appliances and lower handle product product product body product body product pro	DIMENSION		EASURE	
Width of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 37 mm neighbour front more than 90 degrees 37 mm neighbour front more than 90 degrees 38 mm Projection of front in relation to housing of appliance 39 mm appliance, if height is adjustable 30 mm Space in front, which is required to guarantee full operability. The most protruding part gives this 30 mm Grontal handle thickness 30 mm Frontal handle thickness 30 mm Frontal handle thickness 572 mm MAX Height of the product body 572 mm More the product body 572 mm More the product body 574 mm Depth of the product body 574 mm Depth of product excluding protruding interface elements 564 mm	APPLIANCE			
Depth of the front  Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Depth of the product body  572 mm  MAX Height of the product body  546 mm	Height of the front	595	mm	
Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle width  MIN Height of the product body  MAX Height of the product body  MAY Height of the product body  572 mm  Width of the product body  546 mm  Depth of the product excluding protruding interface elements  - mm  - mm  - mm  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width MIN Height of the product body MAX Height of the product body Total handle width Full depth of product body Seption of the opened flap in relation to bearing area Seption of the opened flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is more mounted Lateral projection of opened front at the side where the hinge is fixed Seption of the opened flap in controls when door is opened totally At the side where the hinge is more mounted Lateral projection of opened front at the side where the hinge is fixed Seption of the opened flap in controls when door is opened totally on the projection of front incl. controls whe	Depth of the front	20	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance   18 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable   97 mm Appliance, if height is required to guarantee full operability. The most protruding part gives this dimension   458 mm dimension   458 mm dimension   442 mm Appliance and lower handle   442 mm Appliance width   442 mm Appliance width   442 mm Appliance width   444 mm Appliance width   445 mm	Maximum depth all protruding elements, e.g. handles, controls	41	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle thickness  Frontal handle width  521 mm  MIN Height of the product body  MAX Height of the product body  572 mm  Width of the product body  574 mm  Full depth of product excluding protruding interface elements  - mm  - mm  - mm  - mm  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	, , , , , , , , , , , , , , , , , , ,	37	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm Width of the product body 572 mm Width of the product body 574 mm Upepth of the product body 575 mm Full depth of product excluding protruding interface elements 564 mm	Projection of front in relation to housing of appliance	18	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm Width of the product body 573 mm Width of the product body 574 mm Width of the product body 575 mm Full depth of product excluding protruding interface elements 564 mm mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		5	mm	
dimension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height for the product body Height of product excluding protruding interface elements Height of the product body Hei	When product panel is missing, set to 0	97	mm	
Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm MAX Height of the product body 572 mm Width of the product body 572 mm Unit of the product body 574 mm Depth of the product body 574 mm Full depth of product excluding protruding interface elements 574 mm Full depth of product excluding protruding interface elements 574 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of produ		458	mm	
Frontal handle width 521 mm MIN Height of the product body 572 mm MAX Height of the product body 572 mm Width of the product body 546 mm Depth of the product body 543 mm Full depth of product excluding protruding interface elements 564 mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No  Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door 1 controls when door is opened totally. At the side where the hinge is mounted 1 controls when door is opened totally 2 controls when door is opened totally 3 control	Height from bearing area of appliances and lower handle	442	mm	
MIN Height of the product body 572 mm  MAX Height of the product body 572 mm  Width of the product body 546 mm  Depth of the product body 543 mm  Full depth of product excluding protruding interface elements 564 mm  mm  mm  mm  mm  mm  mm  Appliance Can be used as base for other appliances from the same manufacturer. Default is "No" No  Appliance Flap door  Projection of the opened flap in relation to bearing area 0 mm  Maximum angle when flap door is opened totally 89 mm  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed 0 mm  Maximum angle when door is opened totally 0 mm  Maximum angle when door is opened totally 0 mm  Maximum angle when door is opened totally 0 mm  Maximum angle when door is opened totally 0 mm  Maximum angle when door is opened totally 0 mm  Maximum angle when door is opened totally 0 mm  Appliance other 0 mm	Frontal handle thickness	30	mm	
MAX Height of the product body  Width of the product body  Depth of the product body  Full depth of product excluding protruding interface elements  - mm  mm  mm  mm  mm  Appliance Can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Frontal handle width	521	mm	
Width of the product body  Depth of the product body  Full depth of product excluding protruding interface elements	MIN Height of the product body	572	mm	
Depth of the product body Full depth of product excluding protruding interface elements 564 mm	MAX Height of the product body	572	mm	
Full depth of product excluding protruding interface elements  - mm  - m	Width of the product body	546	mm	
- mm	Depth of the product body	543	mm	
- mm	Full depth of product excluding protruding interface elements	564	mm	
- mm	-	-	mm	
- mm		-	mm	
- mm  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  - mm  - mm  - mm  - mm  0 mm  89 mm  Appliance Side swing door  Lateral projection of pened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  0 mm	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  - mm  Appliance In mm  - mm  Appliance other  - mm  0 mm  Appliance other of the niche to the front end of the freespace of the retrace		-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  0 mm  Maximum angle when flap door is opened totally  89 mm  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  0 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	-	-	mm	
Appliance Flap door  Projection of the opened flap in relation to bearing area 0 mm  Maximum angle when flap door is opened totally 89 mm  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed 0 mm  Maximum angle when door is opened totally 0 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		-	mm	
Projection of the opened flap in relation to bearing area 0 mm  Maximum angle when flap door is opened totally 89 mm  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed 0 mm  Maximum angle when door is opened totally 0 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  O mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Appliance Flap door			
Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  O mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Projection of the opened flap in relation to bearing area	0	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  O mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Maximum angle when flap door is opened totally	89	mm	
mounted  Lateral projection of opened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  0 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Appliance Side swing door			
Maximum angle when door is opened totally 0 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		0	mm	
Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  345 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Maximum angle when door is opened totally	0	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 537 mm	Depth from front end of the niche to the front end of the freespace of the retrace	345	mm	
	Height from niche to bottom end of freespace for the retrace	537	mm	