

W9 MW261 IXL

12NC/Fx: 859991542270

GTIN (EAN) code: 8003437396083

DIMENSION		MEASUR	
OVERALL CABINET			
/IN Height of the wall cabinet niche, including all required space for installation or ventilatio	n 0	mm	
/IN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm	
/IN Height of the base cabinet niche, including all required space for installation or ventilation	on 450	mm	
AX Height of the wall cabinet niche, including all required space for installation or ventilation	on O	mm	
AX Height of the tall cabinet niche, including all required space for installation or ventilation	n 453	mm	
AX Height of the base cabinet niche, including all required space for installation or ventilat	ion 453	mm	
/IN Width of the wall cabinet niche, including all required space for installation or ventilation	n 0	mm	
AIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm	
/IN Width of the base cabinet niche, including all required space for installation or ventilatio	n 560	mm	
AX Width of the wall cabinet niche, including all required space for installation or ventilatio	n 0	mm	
IAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	
AX Width of the base cabinet niche, including all required space for installation or ventilation	on 568	mm	
/IN Depth of the wall cabinet niche, including all required space for installation or ventilatior	n 0	mm	
/IN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm	
/IN Depth of the base cabinet niche, including all required space for installation or ventilation	on 550	mm	
Space in front, which is required to install bottom trim	8	mm	
ndicates whether a ventilation opening is needed or not. Default is "N"	No		
VALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (wall cabinet)	-		
/inimum space or inbound ventilation (wall cabinet)	0	mm	
/inimum area for inbound ventilation cavity (wall cabinet)	0	cm	
VALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (wall cabinet)	-		
/inimum space or outbound ventilation (wall cabinet)	0	mm	
/inimum area for outbound ventilation cavity (wall cabinet)	0	cm	
ALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (tall cabinet)	_		
Animum space for inbound ventilation (tall cabinet)	0	mm	
/inimum area for inbound ventilation cavity (tall cabinet)	0	cm	
ALL CABINET (vent-shaft outgoing)	U	om	
ndicates the position of the freespace for the outbound airflow (tall cabinet)	-		
Animum space for outbound ventilation (tall cabinet)	0	mn	
Animum area for outbound ventilation cavity (tall cabinet)	0	cm	
BASE CABINET (vent-shaft incoming)	Ū	om	
ndicates the position of the freespace for the inbound airflow (base cabinet)	-		
Animum space for inbound ventilation (base cabinet)	0	mm	
Animum area for inbound ventilation cavity (base cabinet)	0	cm ²	
BASE CABINET (vent-shaft outgoing)	U	UII	
ndicates the position of the freespace for the outbound airflow (base cabinet)			
Animum space for outbound ventilation (base cabinet)	- 0	mm	
Animum space for outbound ventilation (base cabinet)	0	mm cm ²	

APPLIANCE		
Height of the front	455	mm
Width of the front	595	mm
Depth of the front	20	mm
Maximum depth all protruding elements, e.g. handles, controls	42	mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	0	mm
Projection of front in relation to housing of appliance	10	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0	mm
When product panel is missing, set to 0	95	mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	348	mm
Height from bearing area of appliances and lower handle	325	mm
Frontal handle thickness	18	mm
Frontal handle width	561	mm
MIN Height of the product body	447	mm
MAX Height of the product body	447	mn
Width of the product body	553	mm
Depth of the product body	535	mn
Full depth of product excluding protruding interface elements	554	mm
Minimum height from bottom line hood to top line air outlet	0	mm
Maximum height from bottom line hood to top line air outlet	0	mn
Diameter minimum air outlet	0	mm
Diameter maximum air outlet	0	mm
Indicates measure between center of air outlet hole and rear wall	0	mm
Projection of the rear flap in relation to bearing area	0	mm
Height tube connection for air outlet	0	mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	-	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	6	mm
Maximum angle when flap door is opened totally	85	mm
Appliance Side swing door		
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm
Lateral projection of opened front at the side where the hinge is fixed	0	mm
Maximum angle when door is opened totally	0	mm
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace	140	mn
Height from niche to bottom end of freespace for the retrace	391	mm